

## Digital Flush Mount Housing (V3.3)

### Specifications

#### Weight:

2.5", 4 digit: 1.0 lb. (0.45 kg)

2.5", 6 digit: 1.4 lb. (0.64 kg)

4.0", 4 digit: 1.71 lb. (0.78 kg)

4.0", 6 digit: 2.2 lb. (1.0 kg)

#### Housing dimensions: (LxWxD)

2.5", 4 digit: 9.63" (24.46 cm) L x 3.75" (9.53 cm) W x 3.00" (7.62 cm) D

2.5", 6 digit: 13.13" (33.35 cm) L x 4.25" (10.80 cm) W x 3.00" (7.62 cm) D

4.0", 4 digit: 12.56" (31.90 cm) L x 6.31" (16.03 cm) W x 3.00" (7.62 cm) D

4.0", 6 digit: 17.81" (45.23 cm) L x 6.18" (15.70 cm) W x 3.00" (7.62 cm) D

#### Mounting:

Flush Mount—The housing is mounted inside of a wall or allocated object like a sign. A hole must be cut into the wall or sign to contain the housing.

#### Material:

Galvanized steel

### Ordering Information:

Digital Flush Mount Housing: SBD-006-XXX-0

Digit Size: 25: 2.5" 40: 4.0"	Digit: 4: 4 Digit 6: 6 Digit
-------------------------------------	------------------------------------

This part number refers to the housing itself, not the actual clock. The ordering information for a complete clock may be found on the digital clock specification sheet. The clock housing is typically included with the clock.

The flush mount housing is only available for Wired and IP digital clocks. Please contact your dedicated Sapling representative for more information.

