

Standard Feature Configurable with Configuration Software <input type="radio"/> Configurable with Hardware Jumper <input type="radio"/> <input checked="" type="radio"/> Configurable with Two Panel Buttons <input type="radio"/>	SBL(C) 3100	SBL(C) 3200	SBL(C) 3300
Digit Size : 2.5" (6.35 cm) or 4.0" (10.16 cm)	●	●	●
Four (00:00) or Six (00:00:00) Digit Display	●	●	●
LED Display Color: Red as standard, with Green, Amber, or White at additional Cost	●	●	●
Single (Surface) Mount or Double Mount	●	●	●
12/24 hour display mode	○	●	○
Alternating Time/Date (3100 - US date format only)	○	●	○
Adjustable Brightness Levels (3100 - 2 levels; 3200/3300 - 4 levels)	○	●	○
Brightness Scheduling		●	●
Capable of displaying numerical messages received from any Sapling Master Clock with a transmitter.	●	●	●
Capable of displaying "Fire" message received from any Sapling Master Clock that is interfacing with fire alarm	●	●	●
Capable of displaying "Bell" messages received from a Sapling 3000 Series Master Clock with at least 4 relays	●	●	●
Capable of receiving a prescheduled countdown command from a Sapling 3000 Series Master Clock with at least 4 relays	●	●	●
Internal lithium coin battery keeps the settings and real time in the event of a power loss/failure.	●	●	●
Powered through 24V, 110VAC, or 230VAC.	●	●	●
UL and cUL compliant	●	●	●
Loss of time signal communication indicated by flashing colon in the digital clock display	●	●	●
Operates on the 915-928MHz - OR - 2.4 GHz (International Use Only) frequency range using frequency-hopping technology	●	●	●
Operates on free license frequency range - no FCC license required.	●	●	●
Receives time signal wirelessly with built-in antenna from either a Sapling SMA 2000 or 3000 Master Clock with transmitter and repeats this signal to other surrounding SBL Digital and SAL Analog Wireless Clocks	●	●	●
Repeats time signal wirelessly once a minute	●	●	●
Capability to interface with Sapling's Configuration Software via USB cable.		●	●
Capability to interface with either Sapling's Elapsed Timer Control Panel to count up/down in real time. - OR - Sapling Temperature Sensor to display in either degrees Celsius or Fahrenheit.		●	●
May trigger a buzzer/alarm (optional accessory) when the Sapling Elapsed Timer reaches 00:00:00.			●
Capability to receive multiple (input) contact closure (signal) from a third party system, such as a Nurse Call system, to trigger elapsed timer functions			●